


F529-7MMGS Finish(GS) ☐

F529-7MMY Finish(Y) ☐



## Specifications

### Features

- 1.8 GPM Flow Rate
- 1, 2, 3 or 4-Hole Installation; Deck Plate or Single Hole Mounting Option
- 2 Function Sprayer
- 360° Rotating Spout
- AccuDock™ Sprayhead Docking
- Forward Handle Operation
- Mounting Hardware Included
- Spot Defense™ Finish Resists Spots and Fingerprints (GS Finish Only)
- Flex-Line Supply Lines
- Quick Install Tool
- Pfaster Connect™
- SoloTilt™ One-Hand Soap Dispenser Included
- Swivel Spout
- TiteSeal™ Deckplate
- Pforever Seal™ Ceramic Disc Valve
- Limited Lifetime Warranty




### Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified to ASME A112.18.1/CSA B125.1 including:
  - ASME A112.18.3 (Backflow Prevention)
- NSF/ANSI/CAN61:Q≤1
- CEC Certified/CALGreen compliant
- ADA Compliant – ANSI A117.1 (Lever Handle Only)




## Dimensions



Ø1-3/8 Min to Ø1-1/2 Max. Deck Hole Openings

### Top Filling Soap Dispenser



### 36 Inch Supply Lines with 3/8 Female Compression Brass Connections

